



### PIN CONNECTIONS

Pin	Symbol	Level	Function
1	FG	-	Frame ground
2	V <sub>SS</sub>	0V	GND
3	V <sub>DD</sub>	+5V	Power supply for logic
4	V <sub>O</sub>	-	Operating voltage for LCD
5	/WR	L	Write signal
6	/RD	L	Read signal
7	/CE	L	Chip enable signal
8	C/D	H/L	“L” Data, “H” Instruction code
9	NC	-	No connection
10	/REST	L	Reset signal ,active “L”
11   18	DB0   DB7	H/L	Data bus line
19	FS	H/L	Font selection: L:8x8,H:6X8
20	V <sub>out</sub>	-	Output voltage for lcd
21	LEDA	+5V	Power supply for LED backlight
22	LEDK	0V	

### NOTES:

- Built-in T6963C controller
- Yellow green mode/blue mode optional

### MECHANICAL DATA

Item	Nominal Dimensions	Unit
Module Size ( W x H x T )	147.8X96.0X16.0	mm
Viewing Area ( W x H )	114.0X64.0	mm
Dot Pitch ( W x H )	0.45X0.45	mm
Dot Size ( W x H )	0.40X0.40	mm

### ABSOLUTE MAXIMUM RATINGS

Item	Symbol	Min.	Max.	Unit
Supply Voltage (Logic)	V <sub>DD</sub> -V <sub>SS</sub>	-0.3	7.0	V
Supply Voltage (LCD)	V <sub>DD</sub> -V <sub>O</sub>	-0.3	17.5	V
Input Voltage	V <sub>I</sub>	-0.3	V <sub>DD</sub> +0.3	V
Operating Temp.	T <sub>OPR</sub>	-20	70	
Storage Temp.	T <sub>STG</sub>	-30	80	

### ELECTRICAL CHARACTERISTICS ( V<sub>DD</sub>=5.0V, Ta=25 )

Item	Symbol	Min.	Typ.	Max.	Unit
Input High Voltage	V <sub>IH</sub>	V <sub>DD</sub> -2.2	-	V <sub>DD</sub>	V
Input Low Voltage	V <sub>IL</sub>	0	-	0.8	V
Output High Voltage	V <sub>OH</sub>	V <sub>DD</sub> -0.3	-	V <sub>DD</sub>	V
Output Low Voltage	V <sub>OL</sub>	0	-	0.3	V
Supply Current	I <sub>DD</sub>	-	15	18	mA
LCD Driving Voltage	V <sub>DD</sub> -V <sub>O</sub>	-	17.1	-	V

### LED BACKLIGHT SPECIFICATIONS ( Ta=25 )

Item	Forward Voltage	Forward Current
YELLOW-GREEN	4.1V	300mA
White	3.1V	150mA