



PIN CONNECTIONS

Pin	Symbol	Level	Function
1	V _{SS}	0V	Ground
2	V _{DD}	5.0V	Power supply for Logic
3	V _O	-	Driving voltage for LCD
4	/WR	L	8080 : Write signal
5	/RD	L	8080 : Read signal
6	/CS	L	Chip select ,Active L
7	A0	H/L	"L" Data, "H" Instruction code
8	/RES	L	Reset signal ,active "L"
9 16	DB0 DB7	H/L	Data bus line
17	NC		No connection
18	V _{EE}	-	Negative Voltage output
19	LEDA	5V	Power supply for LED backlight
20	LEDK	0V	

NOTES:

1. Built-in SED1335/RA8835 controller
2. Temperature compensation optional
3. For CCFL version, the outline dimension is 139.0 X113.8mm

MECHANICAL DATA

Item	Nominal Dimensions	Unit
Module Size (W x H x T)	139.0X105.5X13.0	mm
Viewing Area (W x H)	103.0X79.0	mm
Dot Pitch (W x H)	0.30X0.30	mm
Dot Size (W x H)	0.27X0.27	mm

ABSOLUTE MAXIMUM RATINGS

Item	Symbol	Min.	Max.	Unit
Supply Voltage (Logic)	V _{DD} -V _{SS}	0	6.5	V
Supply Voltage (LCD)	V _{DD} -V _O	0	32	V
Input Voltage	V _I	0	V _{DD}	V
Operating Temp.	T _{OPR}	-20	+70	
Storage Temp.	T _{STG}	-30	+80	

ELECTRICAL CHARACTERISTICS (V_{DD}=5.0V, Ta=25)

Item	Symbol	Min.	Typ.	Max.	Unit
Input High Voltage	V _{IH}	0.5 V _{DD}	-	V _{DD}	V
Input Low Voltage	V _{IL}	0	-	0.2V _{DD}	V
Supply Current	I _{DD}	-	80	-	mA
LCD Driving Voltage	V _{DD} -V _O	-	21.0	-	V

LED BACKLIGHT SPECIFICATIONS (Ta=25)

Item	Forward Voltage	Forward Current
White	3.1V	150mA